


NOTES

- 1 LANE LINES - WIDTH=100mm.
- 2 CENTRE LINE - CONTINUOUS LINE 100mm WIDE.
- 3 CROSSWALK LINES - CONTINUOUS PARALLEL LINES - LINE WIDTH=150mm.
- 4 STOP LINE - 600mm WIDE (FOR INTERSECTION PAVEMENT ARROWS REFER TO AS 17422 FIGURE 4.10)
- 5 SPACING BETWEEN ARROWS - 3 METRES FROM STOP LINE TO FIRST ARROW, 15 METRES FROM FIRST ARROW TO SECOND ARROW AND 15 - 25 METRES FROM THERE ON.

E			GENERAL NOTES / CROSS REFERENCES		 TRAFFIC AND ROAD USE MANAGEMENT DEPARTMENT	STANDARD DRAWING TYPICAL PAVEMENT MARKING - TRAFFIC SIGNALS							
D			UNSPECIFIED DIMENSIONS ARE IN mm.										
C			1 DIMENSIONS BETWEEN STOP LINES AND CROSSWALK										
B			LINES ARE FROM LEADING EDGE TO LEADING EDGE.										
A													
AMEND.	Appd.	DATE	AMENDMENTS		TRAFFIC SYSTEM OPERATION	CHECKED	DATE	APPROVED	DATE	SPEC. REF.	SHEET No.	DRAWING No.	AMENDMENT
						L. FRENCH	13/10/00	B. HEARN	13/10/00			TC - 1001	
						T. S. O. MANAGER							