



NOTES

1. IN UNSEALED AREAS, A COURTESY APRON SHALL BE PROVIDED, CONSISTING OF 80 mm THICK CONCRETE, EXTENDING 600mm AROUND THE FOOTING.
2. CONCRETE STRENGTH GRADE SHALL BE N32 TO THE REQUIREMENTS OF AS-1379 - "SPECIFICATION AND SUPPLY OF CONCRETE".
3. THREADED PORTION OF RAG BOLTS TO BE COATED WITH GRAPHITE GREASE OR SIMILAR AND PROTECTED FROM DAMAGE DURING ASSEMBLY.
4. A CLEARANCE OF 1000mm MUST BE MAINTAINED IN FRONT OF THE CABINET.
5. FOUNDATION TO BE MINIMUM CLEARANCE OF 500mm TO BACK OF KERB AND 200mm FROM BUILDING LINES, POLES etc.

CONDUIT SPECIFICATION (TO AS 2053)

- E100 = ELECTRICAL (ORANGE) HEAVY DUTY CONDUIT 100 dia.
- E50 = ELECTRICAL (ORANGE) HEAVY DUTY CONDUIT 50 dia.
- E20 = ELECTRICAL (ORANGE) HEAVY DUTY CONDUIT 20 dia.

				GENERAL NOTES/CROSS REFERENCES UNSPECIFIED DIMENSIONS ARE IN mm 1. TC-1075 RAG BOLT ASSEMBLY FOR CABINET.		INTELLIGENT TRANSPORT SYSTEMS 60 DENMARK STREET KEW, VICTORIA, 3101 PHONE (03) 9854 2111 FAX (03) 9854 2319		CHECKED S Purhill 24/04/14 APPROVED W Harvey 24/04/14 CAT: PROJ: FILE:				STANDARD DRAWING DISTRIBUTION CABINET TYPE 2 - FOUNDATION DETAIL				
A	SP	23/5/17	CONCRETE APRON INCREASED									FILE NO.	SPEC. REF.	SHEET NO.	DRAWING NO. TC-1074	AMEND. A
AMEND.	APP'D	DATE	AMENDMENT													