



TYPE 2B POST THROUGH VERANDAH WITH 200mm LANTERN AND TARGET BOARD MOUNTED AT STANDARD HEIGHT. SIMILAR PROVISIONS APPLY TO MAST ARMS, JOINT USE MAST ARMS, AND JOINT USE POLES.

TYPE 2A POST WITH TOP SEALED AND CABLES TERMINATING IN JUNCTION BOX. 200mm LANTERN AND TARGET BOARD MOUNTED AT STANDARD HEIGHT. PROVISION FOR EARTHING TO BE REPLACED.

SPECIAL SHORTENED POST WITH TOP SEALED AND CABLES TERMINATING IN JUNCTION BOX. 200mm LANTERN WITHOUT TARGET BOARD MOUNTED. ABSOLUTE MINIMUM CLEARANCE OF 2000 BELOW LANTERN. PROVISION FOR EARTHING TO BE REPLACED.

DRAWINGS NOT TO SCALE

E			GENERAL NOTES / CROSS REFERENCES:		TRAFFIC AND ROAD USE MANAGEMENT DEPARTMENT		STANDARD DRAWING FOR TRAFFIC SIGNALS	
D			1. ALL DIMENSIONS ARE IN mm.		TRAFFIC SYSTEM OPERATION		CHECKED DATE	
C			2. BASE PLATE LOCATED 120 BELOW GROUND.		L. FRENCH 13/10/00		APPROVED DATE	
B			3. MINIMUM VERANDAH HEIGHT FOR STANDARD POSTS:		T. S. O. MANAGER 8 HEARN 13/10/00		SPEC. REF.	
A			2A - 3450				SHEET No.	
			2B - 4300.				DRAWING No.	
AMEND. Appd. DATE			AMENDMENTS			TC - 1126		
						AMENDMENT		