

GENERAL NOTES

1. CONCRETE STRENGTH GRADE SHALL BE N32 TO THE REQUIREMENTS OF AS-1379 - "SPECIFICATION AND SUPPLY OF CONCRETE".
2. THREADED PORTION OF ALL RAG BOLTS TO BE COATED WITH GRAPHITE GREASE OR SIMILAR BEFORE ASSEMBLY.
3. BASE PLATE WILL BE 16MM FOR 2A, 2B AND TYPE 3 PEDESTALS

AMEND.	APP'D	DATE	AMENDMENT
C	SP	1/6/14	ADDITION OF FOAM PAD.
B	SP	4/3/13	CONDUIT DEPTH INCREASED.
A	SP	1/6/14	REVIEW DIMENSIONS (16mm BASE PLATE).

GENERAL NOTES/CROSS REFERENCES
UNSPECIFIED DIMENSIONS ARE IN mm


1. ALL DRAWINGS NOT TO SCALE

INTELLIGENT TRANSPORT SYSTEMS
60 DENMARK STREET KEW, VICTORIA, 3101
PHONE (03) 9854 2111
FAX (03) 9854 2319

CHECKED
L.FRENCH 13/10/00

APPROVED
B.HEARN 13/10/00

CAT:
PROJ:
FILE:



STANDARD DRAWING				
FOUNDATION FOR PEDESTALS				
FILE NO.	SPEC. REF.	SHEET NO.	DRAWING NO.	AMEND.
			TC-1200	C