



NOTES:

1. TRAFFIC SIGNAL AND STREET LIGHTING CONDUITS TO BE ALIGNED AS REQUIRED
2. CONCRETE STRENGTH GRADE SHALL BE N32 TO THE REQUIREMENTS OF AS 1379 - "SPECIFICATION AND SUPPLY OF CONCRETE."

PILE DEPTH	CONCRETE VOLUME m ³	POLE TYPE	RAG BOLTS (TC-1601)
3220	0.9	JUMA JUP MA	HIGH STRENGTH

TABLE 1

				GENERAL NOTES/CROSS REFERENCES UNSPECIFIED DIMENSIONS ARE IN mm		INTELLIGENT TRANSPORT SYSTEMS 60 DENMARK STREET KEW, VICTORIA, 3101 PHONE (03) 9854 2111 FAX (03) 9854 2319		CHECKED APPROVED T.S.O. MANAGER CAT: PROJ: FILE:				STANDARD DRAWING BORED PILE FOR MA, JUP AND JUMA				
B	S.P.	1/6/14	ADDITION OF FOAM PAD.								SCALE OF METRES HOR. NOT TO SCALE VER.	FILE NO.	SPEC. REF.	SHEET NO.	DRAWING NO. TC-1201	AMEND. B
A	S.P.	4/3/13	CONDUIT DEPTH INCREASED.													
AMEND.	APP'D	DATE	AMENDMENT													