



- NOTES:
1. WALL THICKNESS AND REINFORCEMENT SHOWN SHALL APPLY TO ALL PITS UP TO 2400mm DEEP.
 2. ALL REINFORCEMENT LAPS TO BE 300mm LONG.
 3. PITS DEEPER THAN 1200mm AND LESS THAN 2400mm TO BE FITTED WITH STEP-IRONS. PITS DEEPER THAN 2400mm TO BE FITTED WITH LADDER.
 4. STRENGTH OF CONCRETE SHALL BE 25MPa AT 28 DAYS.
 5. ALL DIMENSIONS IN MILLIMETRES UNLESS OTHERWISE SHOWN.
 6. HEAVY DUTY PIT LIDS TO COMPLY WITH AS 3996 - 1992 FOR CLASS D ACCESS COVERS

GENERAL NOTES / CROSS REFERENCES
UNSPECIFIED DIMENSIONS ARE IN mm.

SUPERCEDES DRAWING P864005

STANDARD DRAWING
HEAVY DUTY CABLE PIT
AND COVER

viaRoad
TRAFFIC AND TRANSPORT
INTEGRATION DEPARTMENT
INTELLIGENT TRANSPORT
SYSTEMS GROUP

CHECKED S. PUNITILLI 11.9.03	DATE 11.9.03	APPROVED D. ZABRITZSCH MANAGER ITS	DATE 12.9.03	SPEC. REF.	SHEET No.	DRAWING No. TC-1211	AMENDMENT
---------------------------------	-----------------	--	-----------------	------------	-----------	------------------------	-----------

AMEND.	App'd.	DATE	AMENDMENTS
E			
D			
C			
B			
A			