



PLAN

DETAIL A

SECTION B-B

FOR CABLE PIT INSTALLATION DETAILS REFER TO: TRAFFIC SYSTEM OPERATION STANDARD DRAWING TC-1230

TO TRUNK CONDUIT SYSTEM

MATERIALS REQUIRED PER INSTALLATION

- RAGBOLT ASSEMBLY - M24 COMMERCIAL GRADE
- CABLE PIT FORMER - 600mm DIA.
- CABLE PIT ACCESS COVER AND FRAME - INSCRIBED "VICROADS" AND "COMMUNICATIONS"
- CONDUIT SPECIFICATION - TO AS 2053
- C100 = COMMUNICATIONS (WHITE) HEAVY DUTY CONDUIT 100 DIA.
- C50 = COMMUNICATIONS (WHITE) HEAVY DUTY CONDUIT 50 DIA.
- BENDS TO BE LARGE RADIUS TYPE ONLY.

GENERAL NOTES

1. ALL CONDUITS JOINTS TO BE CEMENTED
2. CONCRETE STRENGTH SHALL BE 25MPa AT 28 DAYS.
3. 50 DIA. AND 100mm CONDUIT TO PROTRUDE 100mm ABOVE FINISHED GROUND LEVEL AND BE LOCATED WITHIN RAGBOLT TEMPLATE AND CENTRALLY LOCATED AS SHOWN.

E		GENERAL NOTES / CROSS REFERENCES	STANDARD DRAWING							
D		ASSOCIATED DRAWINGS	HELP PHONE - TERMINATION PILLAR							
C		TC-1210 CABLE PIT FORMER - 600mm DIA.	INSTALLATION DETAILS							
B		TC-1220 CABLE PIT ACCESS COVER AND FRAME								
A		TC-1230 CABLE PIT - INSTALLATION DETAILS								
		TC-2026 HELP PHONE - TERMINATION PILLAR								
AMEND.	Appd.	DATE	CHECKED	DATE	APPROVED	DATE	SPEC. REF.	SHEET No.	DRAWING No.	AMENDMENT
			J. RANALL	21/12/95	B. HEARN	21/12/95			TC-2027	
			T. S. O. MANAGER							



TRAFFIC AND ROAD USE MANAGEMENT DEPARTMENT

TRAFFIC SYSTEM OPERATION