



NOTES

- FOR GENERAL NOTES REFER DRG No TC-2274
- ALL FLEXIBLE CONDUITS CONNECTING STEEL CONDUIT TO STEEL CONDUIT, STEEL CONDUIT TO JUNCTION BOX AND JUNCTION BOX TO JUNCTION BOX SHALL BE ANACONDA TYPE CONDUIT (IE FLEXIBLE METAL INNER WITH A PVC LINER)
- FABRICATED JUNCTION BOX SHALL BE 1P67 RATED, HAVE GLANDS ON ALL CONDUIT PENETRATIONS
- STANDARD DRAWINGS SHOWN ARE INDICATIVE ONLY. STRUCTURAL DETAILS SHALL BE DESIGNED BY A PRE-QUALIFIED CONSULTANT TO THE SATISFACTION OF VICROADS AND SHALL COMPLY WITH VICROADS' SPECIFICATION BRIDGE TECHNICAL NOTES (BTN'S) AND AS 5100 WHERE APPLICABLE.
- ALL UNUSED CONDUITS SHALL BE CAPPED

| | | | |
|-------|-------|---------|------------------------------|
| E | | | |
| D | | | |
| C | | | |
| B | | | |
| A | W H | 12/2018 | REMOVAL OF STRUCTURAL DETAIL |
| ISSUE | APP'D | DATE | AMENDMENT |

GENERAL NOTES

DESIGNED
M80 UPGRADE 07/2015

APPROVED
W HARVEY - MANAGER
ITS INFRASTRUCTURE & SYSTEM 08/2015

CAT:
PROJ:
FILE:

SCALE OF METRES
NTS

HOR
VER

STANDARD DRAWING
MANAGED MOTORWAY

ACCESSIBLE VMS AND LUMS GANTRY
TYPICAL CONDUIT ROUTE - SHEET 4 OF 6

| | | | | |
|---------|-------------|----------|------------|-------|
| FILE NO | CONTRACT NO | SHEET NO | DRAWING NO | ISSUE |
| | | | TC-2276 | A |