



- NOTES:**
- WHERE ANCHOR IS CAST PRIOR TO BASE, KEY SHALL BE FORMED AS SHOWN AND AGGREGATES ON FACE OF CONSTRUCTION JOINT SHALL BE EXPOSED.
 - ANCHOR BARS AND STIRRUPS: 16mm DIA GRADE 400Y.
 - ANCHOR SHALL EXTEND FULLY ACROSS BASE SLAB.
 - AN APPROVED SEALANT SHALL BE INSTALLED ALONG THE TOP AND DOWN THE VERTICAL EDGES OF THE EXPANSION JOINT.
 - REINFORCEMENT SHALL BE LOCATED IN THE TOP THIRD OF THE BASE AND SHALL HAVE A MINIMUM COVER OF 50 mm.

E			
D			
C	J.C.	1.7.95	GRADE OF ANCHOR BARS & STIRRUPS , GENERAL NOTES 3 & 4
B	M.P.	5.2.90	NOTES 1 & 2 - F82 STEEL FABRIC - ANCHOR
A	M.P.	19.9.89	ANCHOR TAPERED THROUGH SUBBASE
AMEND.	Appd.	Date	AMENDMENTS

GENERAL NOTES / CROSS REFERENCES

- REINFORCEMENT AND TIE BAR ARRANGEMENT AND TRANSVERSE CONSTRUCTION JOINT DETAIL SD 5361
- EXPANSION JOINT DETAIL SD 5401
- SELECTION GUIDE SD 5300
- ALL DIMENSIONS ARE IN MILLIMETRES

vicroads

PRINCIPAL ROAD DESIGN ENGINEER'S DEPARTMENT

STANDARD DRAWING				
CONTINUOUSLY REINFORCED CONC. PAVEMENT (CRCP)				
TERMINAL AT BRIDGE STRUCTURE				
APPROVED <i>Thompson</i> PRINCIPAL RD ENGINEER	DATE 1.7.95	SPEC. REF. No.	SHEET No.	DRAWING No.
		501-521		SD 5391
				AMENDMENT C