



NOTE:
REINFORCEMENT SHALL BE LOCATED IN TOP THIRD OF BASE AND SHALL HAVE A MINIMUM COVER OF 50mm.

E			
D			
C	J.C.	1-7-95	GEN NOTES 1 TO 3, DRG TITLE, NOTE 1 ON PLAN, PAVEMENT DRAIN AND SUBGRADE BEAM.
B	M.P.	15.3.90	SECTION A-A NOTES
A	M.P.	5.2.90	TRAFFIC SIGNAL DETECTOR LOOP INST. ADDED
AMEND.	Appd.	Date	AMENDMENTS

GENERAL NOTES / CROSS REFERENCES

1. TRANSVERSE JUNCTION OF CONCRETE AND FLEXIBLE PAVEMENTS. SD 5352, SD 5381
2. SELECTION GUIDE SD 5300
3. ALL DIMENSIONS ARE IN MILLIMETRES.

vicroads

PRINCIPAL ROAD DESIGN ENGINEER'S DEPARTMENT

STANDARD DRAWING				
CONCRETE PAVEMENT - ALL TYPES				
LONGITUDINAL JUNCTION WITH FLEXIBLE PAVEMENT AND TRAFFIC SIGNAL DETECTOR LOOP INSTALLATION				
APPROVED	DATE	SPEC. REF. No.	SHEET No.	DRAWING No.
<i>J. Cunningham</i>	1-7-95	501-521		SD 5421
PRINCIPAL RD ENGINEER				C