



HEAVY DUTY STOCK PROOF FENCE

NOTES:

1. POSTS 50 N.B. LIGHT PIPE (60.3 O.D.) GRADE 350
2. HEAVY DUTY STOCK PROOF FENCE - 3 No. 40 N.B. XL PIPE GRADE 350 AT FIRST, SECOND AND THIRD ROWS
- 4 No. 25 N.B. XL PIPE GRADE 350 AT FORTH, FIFTH SIXTH AND SEVENTH ROWS
- 1 No. 40mm x 5mm STRAP
3. TO BE INSTALLED ON STOCK ROUTES AT STOCK UNDERPASSES
4. INSITU CONCRETE SHALL BE 20MPa STRENGTH GRADE COMPLYING WITH THE REQUIREMENTS OF AS 1379/1991

E			
D			
C			
B			
A			
ISSUE	APP'D	DATE	AMENDMENT

GENERAL NOTES 1. ALL DIMENSIONS ARE IN MILLIMETRES.
2. THIS DRAWING IS PROVIDED AS A GUIDE FOR GOOD FENCING PRACTICE. PROPERTY OWNERS MAY AGREE TO THE ERECTION OF A STANDARD FENCE OF SIMILAR TYPE TO THE EXISTING FENCE AS AN ALTERNATIVE.

DESIGNED PRINCIPAL ROAD DESIGN ENGINEER
APPROVED *[Signature]* Date 1/8/02
CATALOG: PRED
PROJECT: sddgnnew

COMPUTER FILE sd-3103.dgn
SCALE OF METRES
HOR NOT TO SCALE
VER



STANDARD DRAWING
HEAVY DUTY STOCK PROOF FENCE
FILE NO. CONTRACT NO. SHEET NO. DRAWING NO. SD 3103 ISSUE