



NOTES

1. IN UNSEALED AREAS, A COURTESY APRON SHALL BE PROVIDED, CONSISTING OF 80 mm THICK CONCRETE, EXTENDING 200mm AROUND THE FOOTING, EXCEPT IN FRONT OF THE DOOR WHERE THE APRON SHALL BE 600mm WIDE.
2. STRENGTH OF CONCRETE SHALL BE 25 MPa AT 28 DAYS.
3. THREADED PORTION OF RAG BOLTS TO BE COATED WITH GRAPHITE GREASE OR SIMILAR AND PROTECTED FROM DAMAGE DURING ASSEMBLY.

CONDUIT SPECIFICATION

- E/100 = ELECTRICAL (ORANGE) HEAVY DUTY CONDUIT 100 dia.
- E/50 = ELECTRICAL (ORANGE) HEAVY DUTY CONDUIT 50 dia.
- C/100 = COMMUNICATION (WHITE) HEAVY DUTY CONDUIT 100 dia.

E			
D			
C	13/02/2013	BOLT DIMS (SECT A & B) AMENDED. TITLE BLOCK UPDATED	
B	KW	6/2/2004	NAME CHANGE TO FREEWAY DATA STATION (FORMERLY ID)
A	LW	11/5/1999	FOUNDATION DIMENSIONS CHANGED
AMEND.	Appd.	DATE	AMENDMENTS

GENERAL NOTES / CROSS REFERENCES
 UNSPECIFIED DIMENSIONS ARE IN mm.
 DRAWING NOT TO SCALE

1- ALL DIMENSIONS ARE IN MILLIMETRES UNLESS OTHERWISE SHOWN.
 2- TC-1603 RAG BOLT ASS'Y FOR CABINET.
 3- TC-2003 CABINET



ROAD USER SERVICES
 TRANSPORT SYSTEMS OPERATIONS
 GROUND FLOOR, 60 DENMARK ST, KEW, 3101

CHECKED DATE J. RANDALL 21/12/95		APPROVED DATE B. HEARN 21/12/95 MANAGER TSO		SPEC-REF.	SHEET No.	DRAWING No.	AMENDMENT
						TC-2002	C

STANDARD DRAWING
 CABINET - INSTALLATION DETAILS
 FREEWAY DATA STATION